

## **Product data**

## for design verfication according to IEC / EN 61439-1

| Product description  |  |
|--|--|
| Part No.   | 31173                                      |
| Description 1  | D fuse base, panel-mounting                |
| Description 2  | E 27 / 25 A / 1P, for screw-in gauge rings |
| Description 3  | touch protected acc. to DGUV V3            |
| Size   | DII E27                                    |
| Rated current (IEC)  | 25 A                                       |
| Rated voltage (IEC) AC                                       | 500 V                                      |
| Rated voltage (IEC) DC                                       | 500 V                                      |
| Power dissipation at rated uninterrupted current of the item | 0.7 W                                      |

| Produc   | Product features for design verification<br>Construction   |  |  |
|----------|--|--|--|
| Constru  |  |  |  |
| 10.2     | Strength of materials and parts  | see following subitems   |  |
| 10.2.2   | Resistance to corrosion  | Requirements fulfilled<br>Wöhner products are electrical equipment for which the<br>respective product standard is to be applied.<br>The single parts made out of ferrous metals are protected<br>efficiently against corrosion.     |  |
| 10.2.3   | Properties of insulating materials   | see following subitems   |  |
| 10.2.3.3 | 1 Verification of thermal stability of<br>enclosures   | Wöhner products do not represent an enclosure. However, the required heat resistance of 70° is fulfilled.  |  |
| 10.2.3.2 | 2 Verification of resistance of<br>insulating materials to abnormal<br>heat and fire due to internal<br>electric effects | Requirements fulfilled (glow wire test)<br>parts necessary to retain current carrying parts in position:<br>960°C<br>other parts: 650 °C   |  |
| 10.2.4   | Resistance to ultra-violet (UV)<br>radiation   | only applicable for outdoor installations<br>not relevant, since Wöhner components are generally not<br>used as external parts   |  |
| 10.2.5   | Lifting  | not relevant, since the whole assembly must be evaluated   |  |
| 10.2.6   | Mechanical impact  | not relevant, only applicable for enclosures   |  |
| 10.2.7   | Marking  | requirements fulfilled   |  |
| 10.3     | Degree of protection of<br>enclosures  | not relevant, only applicable for enclosures   |  |
| 10.4     | Clearances and creepage distances  | the requirements are fulfilled for the single Wöhner components  |  |
| 10.5     | Protection against electric shock<br>and integrity of protective circuits  | lies within the responsibility of the assembler  |  |
| 10.6     | Incorporation of switching devices and components  | lies within the responsibility of the panel builder<br>the requirements are fulfilled for the single Wöhner<br>components, as long as they are used as intended and<br>Wöhner's mounting and operating instructions are<br>respected |  |

| 10.7   | Internal electrical circuits and connections         | lies within the responsibility of the panel builder<br>the requirements are fulfilled for the single Wöhner<br>components, as long as they are used as intended and<br>Wöhner's mounting and operating instructions are<br>respected   |  |
|--------|--|--|--|
| 10.8   | Terminals for external conductors                    | lies within the responsibility of the panel builder<br>the requirements are fulfilled for the single Wöhner<br>components, as long as they are used as intended and<br>Wöhner's mounting and operating instructions are<br>respected   |  |
| Behavi | Behaviour  |  |  |
| 10.9   | Dielectric properties                                | see following subitems   |  |
| 10.9.1 | General  | lies within the responsibility of the panel builder<br>the requirements are fulfilled for the single Wöhner<br>components, as long as they are used as intended and<br>Wöhner's mounting and operating instructions are<br>respected   |  |
| 10.9.2 | Power-frequency withstand voltage                    |  |  |
| 10.9.3 | Impulse withstand voltage                            | 6 kV   |  |
| 10.9.4 | Testing of enclosures made of<br>insulating material | not relevant, since the whole assembly must be evaluated   |  |
| 10.9.5 | External conditions of insulating material           | not relevant   |  |
| 10.10  | Verification of temperature rise                     | the single Wöhner components meet the temperature rise<br>requirements of the the product standards as long as they<br>are used as intended.<br>Additionally, evidence must be provided for the switchgear<br>combination or for parts of it. Power dissipations of the<br>Wöhner components can be used here. |  |
| 10.11  | Short-circuit withstand strength                     | cond. rated short-circuit current with fuses:<br>50 kA / 500 V AC<br>8 kA / 500 V DC   |  |
| 10.12  | Electromagnetic compatibility (EMC)                  | lies within the responsibility of the assembler  |  |
| 10.13  | Mechanical operation                                 | lies within the responsibility of the panel builder<br>the requirements are fulfilled for the single Wöhner<br>components, as long as they are used as intended and<br>Wöhner's mounting and operating instructions are<br>respected   |  |

For further information see: http://www.woehner.com/en/products/31173.html