



31 241

Pro pojistkovou techniku s válcovými pojistkami třídy CC

Pojistkové vložky třídy CC time delay (pomalé)

odpovídá UL 248-4



Velikost	Jm. proud A	Jm. napětí V AC	Jm. vypínačí schopnost kA		Balení	Hmotnost kg/%	Obrázek	Obj. č.
Třída CC (10 x 38) pomalé	0,5	600	200		10	0,8		31 394
	1,0	600	200		10	0,8		31 244
	1,5	600	200		10	0,8		31 395
	2,0	600	200		10	0,8		31 245
	2,5	600	200		10	0,8		31 396
	3,0	600	200		10	0,8		31 397
	4,0	600	200		10	0,8		31 246
	5,0	600	200		10	0,8		31 398
	6,0	600	200		10	0,8		31 247
	8,0	600	200		10	0,8		31 399
	10,0	600	200		10	0,8		31 248
	12,0	600	200		10	0,8		31 400
	15,0	600	200		10	0,8		31 249
	20,0	600	200		10	0,8		31 250
	25,0	600	200		10	0,8		31 251
	30,0	600	200		10	0,8		31 252

Pojistkové vložky třídy CC fast acting (rychlé)

odpovídá UL 248-4



Třída CC (10 x 38) rychlé	0,5	600	200		10	0,8		31 401
	1,0	600	200		10	0,8		31 235
	1,5	600	200		10	0,8		31 402
	2,0	600	200		10	0,8		31 236
	2,5	600	200		10	0,8		31 403
	3,0	600	200		10	0,8		31 404
	4,0	600	200		10	0,8		31 237
	5,0	600	200		10	0,8		31 405
	6,0	600	200		10	0,8		31 238
	8,0	600	200		10	0,8		31 406
	10,0	600	200		10	0,8		31 239
	12,0	600	200		10	0,8		31 407
	15,0	600	200		10	0,8		31 240
	20,0	600	200		10	0,8	x	31 241
	25,0	600	200		10	0,8		31 242
	30,0	600	200		10	0,8		31 243